

Specification	RT-2015	RT-2016
Processor	Intel Bay Trail J1900 Quad Core CPU, up to 2.42 GHz, 2M Cache	
System Memory	DDR3L SO-DIMM slot x 1, max. 8GB	
Storage Device	SATA storage x 2	
Power Supply	12V/60W	
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request	
Display & Touch		
LCD	15" TFT LCD	15.6" TFT LCD
Resolution	1024 x 768	1920 x 1080
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)	
I/O & Expansion		
Serial Port	3, DB9 x 1 + RJ50 x 2, 5V/12V support on all COM ports	
Standard USB Port	5, USB 3.0 x 1 + USB 2.0 x 4	
LAN Port	10/100/1000 Mb x 1	
Display Port	VGA via proprietary connector (12V support for Posiflex monitors) x 1 + mini DP x 1	
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer	
Audio	Internal 2W speaker x 1	
Expansion Slot	M.2 slot x 1	
Physical Dimension		
Dimension (W x D x H in mm)	368 x 207 x 325	402 x 207 x 297
Weight (N. W. in kg)	5.4	5
Environmental		
Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	
Built-in Options		
WiFi	M.2 WiFi/BT module	
Camera	1MP wide angle camera	
AG Glass	Cannot coexist with built-in camera	
Expandable USB Module	USB 2.0 x 4 (USB 3.0 x 1 from the system will no longer be available with the USB extension module)	
Expandable PoweredUSB Module	24V x 1 + 12V x 1 (USB 3.0 x 1 from the system will no longer be available with the PoweredUSB extension module)	
UPS Battery Backup	UPS pack for RT Series	
Attachment Options		
POS Monitor	9.7" / 10.1" TFT LCD display (touch/non-touch)	
Line Display	2 x 20 rear-mount VFD customer line display	

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

*Please refer to the website for more attachment options.



EN201809V5



POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller



Make Your Business Look More Attractive

RT-2015/2016

Fanless POS Terminal



Slim & Stylish Look

With stylish, fluid contours for its base and true-flat design, the RT-2000 Series has 15" or 15.6" PCAP touch screen, and full suite of ports that are hidden in the clean rear cover. No screws can be found on its surface maintaining a neat and sleek look.

Patented Fanless Technology

The patented fanless technology allows the terminal to run quietly in all kinds of harsh conditions and – at the same time - provides a long service life.



Fanless
Technology



Dust
Resistant




Water
Resistant



Money
Saving



Full HD
15.6"



Clean Cable Management

Advanced cable management design delivers a truly clutter-free station. The standard base can house the optional Powered USB or USB extension module, while the optional base integrates a UPS backup (RB-5000) for the event of a power failure.



Expandable
USB Module

Serviceability & Shipment with Ease

Rear cover can be removed easily and without tools, thus allowing for faster installation and serviceability. The unit can be shipped with line display or 9.7" / 10.1" 2nd customer facing LCD display attached and folded, saving deployment time as well as shipping costs.